

# globus openssl module

## 3.2

Generated by Doxygen 1.8.4

Sat Aug 3 2013 18:15:14

## Contents

<b>1</b>	<b>Globus OpenSSL activation/deactivation</b>	<b>1</b>
<b>2</b>	<b>Module Index</b>	<b>1</b>
2.1	Modules . . . . .	1
<b>3</b>	<b>Module Documentation</b>	<b>1</b>
3.1	Activation . . . . .	1
3.1.1	Detailed Description . . . . .	1
3.1.2	Macro Definition Documentation . . . . .	2
	<b>Index</b>	<b>3</b>

## 1 Globus OpenSSL activation/deactivation

The globus\_openssl library is motivated by the desire to make OpenSSL thread safe. This is done by allocating a mutex pool and setting relevant callback functions in the module activation functions.

Any program that uses OpenSSL functions must include "globus\_openssl.h".

## 2 Module Index

### 2.1 Modules

Here is a list of all modules:

<b>Activation</b>	<b>1</b>
-------------------	----------

## 3 Module Documentation

### 3.1 Activation

#### Macros

- #define **GLOBUS\_OPENSSL\_MODULE**

#### 3.1.1 Detailed Description

Globus OpenSSL uses standard Globus module activation and deactivation. Before any OpenSSL functions are called, the following function must be called:

```
globus_module_activate(GLOBUS_OPENSSL_MODULE)
```

This function returns `GLOBUS_SUCCESS` if OpenSSL was successfully initialized, and you are therefore allowed to subsequently call OpenSSL functions. Otherwise, an error code is returned, and OpenSSL functions should not subsequently be called. This function may be called multiple times.

To deactivate the OpenSSL module , the following function must be called:

```
globus_module_deactivate(GLOBUS_OPENSSL_MODULE)
```

This function should be called once for each time OpenSSL was activated.

### **3.1.2 Macro Definition Documentation**

#### **3.1.2.1 #define GLOBUS\_OPENSSL\_MODULE**

Module descriptor.

## Index

Activation, 1

    GLOBUS\_OPENSSL\_MODULE, 2

GLOBUS\_OPENSSL\_MODULE

    Activation, 2