

NAME

gv_php - graph manipulation in php

SYNOPSIS

```
#!/usr/bin/php
<?
include("gv.php")
?>
```

USAGE**INTRODUCTION**

gv_php is a dynamically loaded extension for **php** that provides access to the graph facilities of **graphviz**.

COMMANDS**New graphs**

New empty graph

```
graph_handle gv::graph (name);
graph_handle gv::digraph (name);
graph_handle gv::strictgraph (name);
graph_handle gv::strictdigraph (name);
```

New graph from a dot-syntax string or file

```
graph_handle gv::readstring (string);
graph_handle gv::read (string filename);
graph_handle gv::read (channel);
```

Add new subgraph to existing graph

```
graph_handle gv::graph (graph_handle, name);
```

New nodes

Add new node to existing graph

```
node_handle gv::node (graph_handle, name);
```

New edges

Add new edge between existing nodes

```
edge_handle gv::edge (tail_node_handle, head_node_handle);
```

Add a new edge between an existing tail node, and a named head node which will be induced in the graph if it doesn't already exist

```
edge_handle gv::edge (tail_node_handle, head_name);
```

Add a new edge between an existing head node, and a named tail node which will be induced in the graph if it doesn't already exist

```
edge_handle gv::edge (tail_name, head_node_handle);
```

Add a new edge between named tail and head nodes which will be induced in the graph if they don't already exist

```
edge_handle gv::edge (graph_handle, tail_name, head_name);
```

Setting attribute values

Set value of named attribute of graph/node/edge - creating attribute if necessary

```
string gv::setv (graph_handle, attr_name, attr_value);
string gv::setv (node_handle, attr_name, attr_value);
string gv::setv (edge_handle, attr_name, attr_value);
```

Set value of existing attribute of graph/node/edge (using attribute handle)

```
string gv::setv (graph_handle, attr_handle, attr_value);
string gv::setv (node_handle, attr_handle, attr_value);
string gv::setv (edge_handle, attr_handle, attr_value);
```

Getting attribute values

Get value of named attribute of graph/node/edge

```
string gv::getv (graph_handle, attr_name);
string gv::getv (node_handle, attr_name);
string gv::getv (edge_handle, attr_name);
```

Get value of attribute of graph/node/edge (using attribute handle)

```
string gv::getv (graph_handle, attr_handle);
string gv::getv (node_handle, attr_handle);
string gv::getv (edge_handle, attr_handle);
```

Obtain names from handles

```
string gv::nameof (graph_handle);
string gv::nameof (node_handle);
string gv::nameof (attr_handle);
```

Find handles from names

```
graph_handle gv::findsubg (graph_handle, name);
node_handle gv::findnode (graph_handle, name);
edge_handle gv::findedge (tail_node_handle, head_node_handle);
attribute_handle gv::findattr (graph_handle, name);
attribute_handle gv::findattr (node_handle, name);
attribute_handle gv::findattr (edge_handle, name);
```

Misc graph navigators returning handles

```
node_handle gv::headof (edge_handle);
node_handle gv::tailof (edge_handle);
graph_handle gv::graphof (graph_handle);
graph_handle gv::graphof (edge_handle);
graph_handle gv::graphof
```